

Technical specs

MA400 - MA400

Name:

PVC-COATED POLYESTER RAINCOAT

Size:

M - L - XL - XXL

Colour:

Green - Yellow

**Description :**

Rain coat. Sealed seams. Fixed hood. Fastening with double press-studs flap. Raglan sleeves. Elasticated inside cuffs. 2 pockets.

Materials:

PVC-coated 100% polyester support internal side 190 gr/m².

Strong points:

Ventilation back flap.
Underarm ventilation eyelets.
Decorative retro-reflective bands (front and back).

Instructions for use:

Rain garment designed to be used under neither exceptional nor extreme weather conditions. Protection only against minimal hazards.

Limits to use:

Do not use this raincoat for other protections than those against weather conditions. Before putting on this garment, check that it's not dirty or worn, it would be less effective. For optimum protection rain coat must be worn closed. This garment contains no known carcinogenic or toxic substances, or substances which may cause allergies in sensitive people. The following Table is a guide to illustrate the effect of water vapour permeability on the recommended continuous wearing time of a garment in different ambient temperatures. Recommended maximum continuous wearing time for a complete suit consisting of jacket and trousers without thermal lining

Temperature of working environment	Class 1* Ret > 40	Class 2 20 < Ret ≤ 40	Class 3 Ret ≤ 20
25°C	60 min	105 min	205 min
20°C	75 min	250 min	-
15°C	100 min	-	-
10°C	240 min	-	-
5°C	-	-	-

" - " = no limit for wearing time. Table valid for medium physiological strain ($M = 150 \text{ W/m}^2$), standard-man, at 50 % relative humidity. and wind speed $V_a = 0,5 \text{ m/s}$. With effective ventilation openings and/or break periods the time for wearing can be prolonged. (*) For clothing having a class 1 in Ret (evaporative resistance), the wearing time must be limited according to the temperature of the environment of work in accordance with the table above.

Instructions for storage:

Keep in its original packing away from light and humidity. Environment: The item of protection may be discarded with the household waste. The lifespan of the garment depends on its general conditions after use (wear, etc...).

Technical specs

MA400 - MA400

Instructions for cleaning / maintenance:

Wash with a humid sponge, do not machine wash, maximum temperature: 40°C, handle with care. No bleach. Do not iron, steam processes are forbidden. Do not dry clean, do not remove stains with solvents. Do not tumble dry. Environmental conditions such as cold and heat, chemical products, sunlight or incorrect use, may significantly affect the protective performances and lifespan of this garment. Stop using this article upon signs of deterioration and replace it with a new article.

Performances :

This raincoat complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility and fulfills the requirements of the European standards EN340:2003 & EN343:2003 (3,1*).

- **EN343:2003** Protective garment against rain exposures



3 : Resistance of the Penetration of water (1 to 3)

1* : Evaporative resistance (1 to 3)